

 Close this window

SDS

Common Name: SHC 630**Manufacturer:** EXXON MOBIL**SDS Revision Date:** 3/17/2015**SDS Format:** GHS-US**Item Number(s):** 20JY58, 6Y778**Manufacturer Model Number(s):**

SDS Table of Contents

Click the desired link below to jump directly to that section in the SDS.

[SECTION 1 PRODUCT AND COMPANY IDENTIFICATION](#)[SECTION 2 HAZARDS IDENTIFICATION](#)[SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS](#)[SECTION 4 FIRST AID MEASURES](#)[SECTION 5 FIRE FIGHTING MEASURES](#)[SECTION 6 ACCIDENTAL RELEASE MEASURES](#)[SECTION 7 HANDLING AND STORAGE](#)[SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION](#)[SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES](#)[SECTION 10 STABILITY AND REACTIVITY](#)[SECTION 11 TOXICOLOGICAL INFORMATION](#)[SECTION 12 ECOLOGICAL INFORMATION](#)[SECTION 13 DISPOSAL CONSIDERATIONS](#)[SECTION 14 TRANSPORT INFORMATION](#)[SECTION 15 REGULATORY INFORMATION](#)[SECTION 16 OTHER INFORMATION](#)

EXXONMOBIL

PRODUCT NAME: MOBIL SHC 630

REVISION DATE: 17 MAR 2015

SAFETY DATA SHEET

SECTION 1 PRODUCT AND COMPANY IDENTIFICATION



PRODUCT:

PRODUCT NAME: MOBIL SHC 630

PRODUCT DESCRIPTION: SYNTHETIC BASE STOCKS AND ADDITIVES

PRODUCT CODE: 201560500550, 602953-00, 970782

INTENDED USE: CIRCULATING/GEAR OIL

COMPANY IDENTIFICATION:

SUPPLIER:

EXXON MOBIL CORPORATION
22777 SPRINGWOODS VILLAGE PARKWAY
SPRING, TX. 77389
USA

24 HOUR HEALTH EMERGENCY: 609-737-4411

TRANSPORTATION EMERGENCY PHONE: 800-424-9300 OR 703-527-3887 CHEMTREC

PRODUCT TECHNICAL INFORMATION: 800-662-4525

MSDS INTERNET ADDRESS:

HTTP://WWW.EXXON.COM

HTTP://WWW.MOBIL.COM

SECTION 2 HAZARDS IDENTIFICATION



THIS MATERIAL IS NOT HAZARDOUS ACCORDING TO REGULATORY GUIDELINES
(SEE (M)SDS SECTION 15).

OTHER HAZARD INFORMATION:

HAZARD NOT OTHERWISE CLASSIFIED (HNOC):
NONE AS DEFINED UNDER 29 CFR 1910.1200.

PHYSICAL / CHEMICAL HAZARDS: NO SIGNIFICANT HAZARDS.

HEALTH HAZARDS:

HIGH-PRESSURE INJECTION UNDER SKIN MAY CAUSE SERIOUS DAMAGE. EXCESSIVE
EXPOSURE MAY RESULT IN EYE, SKIN, OR RESPIRATORY IRRITATION.

ENVIRONMENTAL HAZARDS: NO SIGNIFICANT HAZARDS.

NFPA HAZARD ID:

HEALTH 0
FLAMMABILITY 1
REACTIVITY 0

HMIS HAZARD ID:

HEALTH 0
FLAMMABILITY 1
REACTIVITY 0

NOTE:

THIS MATERIAL SHOULD NOT BE USED FOR ANY OTHER PURPOSE THAN THE INTENDED
USE IN SECTION 1 WITHOUT EXPERT ADVICE. HEALTH STUDIES HAVE SHOWN THAT
CHEMICAL EXPOSURE MAY CAUSE POTENTIAL HUMAN HEALTH RISKS WHICH MAY VARY
FROM PERSON TO PERSON.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS



THIS MATERIAL IS DEFINED AS A MIXTURE.

HAZARDOUS SUBSTANCE(S) OR COMPLEX SUBSTANCE(S) REQUIRED FOR DISCLOSURE:

NAME	CAS#	CONCENTRATION*	GHS HAZARD CODES
1-DECENE, HOMOPOLYMER HYDROGENATED	68037-01-4	20 - <30%	H304
TRIPHENYL PHOSPHATE	115-86-6	<0.25%	H400(M FACTOR 1), H410(M FACTOR 1)

* ALL CONCENTRATIONS ARE PERCENT BY WEIGHT UNLESS MATERIAL IS A GAS.
GAS CONCENTRATIONS ARE IN PERCENT BY VOLUME.

AS PER PARAGRAPH (I) OF 29 CFR 1910.1200, FORMULATION IS CONSIDERED A
TRADE SECRET AND SPECIFIC CHEMICAL IDENTITY AND EXACT PERCENTAGE
(CONCENTRATION) OF COMPOSITION MAY HAVE BEEN WITHHELD. SPECIFIC CHEMICAL
IDENTITY AND EXACT PERCENTAGE COMPOSITION WILL BE PROVIDED TO HEALTH
PROFESSIONALS, EMPLOYEES, OR DESIGNATED REPRESENTATIVES IN ACCORDANCE WITH
APPLICABLE PROVISIONS OF PARAGRAPH (I).

SECTION 4 FIRST AID MEASURES



INHALATION:

REMOVE FROM FURTHER EXPOSURE. FOR THOSE PROVIDING ASSISTANCE, AVOID EXPOSURE TO YOURSELF OR OTHERS. USE ADEQUATE RESPIRATORY PROTECTION. IF RESPIRATORY IRRITATION, DIZZINESS, NAUSEA, OR UNCONSCIOUSNESS OCCURS, SEEK IMMEDIATE MEDICAL ASSISTANCE. IF BREATHING HAS STOPPED, ASSIST VENTILATION WITH A MECHANICAL DEVICE OR USE MOUTH-TO-MOUTH RESUSCITATION.

SKIN CONTACT:

WASH CONTACT AREAS WITH SOAP AND WATER. IF PRODUCT IS INJECTED INTO OR UNDER THE SKIN, OR INTO ANY PART OF THE BODY, REGARDLESS OF THE APPEARANCE OF THE WOUND OR ITS SIZE, THE INDIVIDUAL SHOULD BE EVALUATED IMMEDIATELY BY A PHYSICIAN AS A SURGICAL EMERGENCY. EVEN THOUGH INITIAL SYMPTOMS FROM HIGH PRESSURE INJECTION MAY BE MINIMAL OR ABSENT, EARLY SURGICAL TREATMENT WITHIN THE FIRST FEW HOURS MAY SIGNIFICANTLY REDUCE THE ULTIMATE EXTENT OF INJURY.

EYE CONTACT:

FLUSH THOROUGHLY WITH WATER. IF IRRITATION OCCURS, GET MEDICAL ASSISTANCE.

INGESTION:

FIRST AID IS NORMALLY NOT REQUIRED. SEEK MEDICAL ATTENTION IF DISCOMFORT OCCURS.

SECTION 5 FIRE FIGHTING MEASURES



EXTINGUISHING MEDIA:

APPROPRIATE EXTINGUISHING MEDIA:

USE WATER FOG, FOAM, DRY CHEMICAL OR CARBON DIOXIDE (CO2) TO EXTINGUISH FLAMES.

INAPPROPRIATE EXTINGUISHING MEDIA: STRAIGHT STREAMS OF WATER

FIRE FIGHTING:

FIRE FIGHTING INSTRUCTIONS:

EVACUATE AREA. PREVENT RUNOFF FROM FIRE CONTROL OR DILUTION FROM ENTERING STREAMS, SEWERS, OR DRINKING WATER SUPPLY. FIREFIGHTERS SHOULD USE STANDARD PROTECTIVE EQUIPMENT AND IN ENCLOSED SPACES, SELF-CONTAINED BREATHING APPARATUS (SCBA). USE WATER SPRAY TO COOL FIRE EXPOSED SURFACES AND TO PROTECT PERSONNEL.

HAZARDOUS COMBUSTION PRODUCTS:

OXIDES OF CARBON, SMOKE, FUME, SULFUR OXIDES, ALDEHYDES, INCOMPLETE COMBUSTION PRODUCTS

FLAMMABILITY PROPERTIES:

FLASH POINT [METHOD]: >210 DEG. C (410 DEG. F) [ASTM D-92]

FLAMMABLE LIMITS (APPROXIMATE VOLUME % IN AIR):

LEL: 0.9

UEL: 7.0

AUTOIGNITION TEMPERATURE: N/D

SECTION 6 ACCIDENTAL RELEASE MEASURES



NOTIFICATION PROCEDURES:

IN THE EVENT OF A SPILL OR ACCIDENTAL RELEASE, NOTIFY RELEVANT AUTHORITIES IN ACCORDANCE WITH ALL APPLICABLE REGULATIONS. US REGULATIONS REQUIRE REPORTING RELEASES OF THIS MATERIAL TO THE ENVIRONMENT WHICH EXCEED THE APPLICABLE REPORTABLE QUANTITY OR OIL SPILLS WHICH COULD REACH ANY WATERWAY INCLUDING INTERMITTENT DRY CREEKS. THE NATIONAL RESPONSE CENTER CAN BE

REACHED AT (800)424-8802.

PROTECTIVE MEASURES:

AVOID CONTACT WITH SPILLED MATERIAL. SEE SECTION 5 FOR FIRE FIGHTING INFORMATION. SEE THE HAZARD IDENTIFICATION SECTION FOR SIGNIFICANT HAZARDS. SEE SECTION 4 FOR FIRST AID ADVICE. SEE SECTION 8 FOR ADVICE ON THE MINIMUM REQUIREMENTS FOR PERSONAL PROTECTIVE EQUIPMENT. ADDITIONAL PROTECTIVE MEASURES MAY BE NECESSARY, DEPENDING ON THE SPECIFIC CIRCUMSTANCES AND/OR THE EXPERT JUDGMENT OF THE EMERGENCY RESPONDERS.

SPILL MANAGEMENT:

LAND SPILL:

STOP LEAK IF YOU CAN DO IT WITHOUT RISK. RECOVER BY PUMPING OR WITH SUITABLE ABSORBENT.

WATER SPILL:

STOP LEAK IF YOU CAN DO IT WITHOUT RISK. CONFINE THE SPILL IMMEDIATELY WITH BOOMS. WARN OTHER SHIPPING. REMOVE FROM THE SURFACE BY SKIMMING OR WITH SUITABLE ABSORBENTS. SEEK THE ADVICE OF A SPECIALIST BEFORE USING DISPERSANTS.

WATER SPILL AND LAND SPILL RECOMMENDATIONS ARE BASED ON THE MOST LIKELY SPILL SCENARIO FOR THIS MATERIAL; HOWEVER, GEOGRAPHIC CONDITIONS, WIND, TEMPERATURE, (AND IN THE CASE OF A WATER SPILL) WAVE AND CURRENT DIRECTION AND SPEED MAY GREATLY INFLUENCE THE APPROPRIATE ACTION TO BE TAKEN. FOR THIS REASON, LOCAL EXPERTS SHOULD BE CONSULTED.

NOTE: LOCAL REGULATIONS MAY PRESCRIBE OR LIMIT ACTION TO BE TAKEN.

ENVIRONMENTAL PRECAUTIONS:

LARGE SPILLS:

DIKE FAR AHEAD OF LIQUID SPILL FOR LATER RECOVERY AND DISPOSAL. PREVENT ENTRY INTO WATERWAYS, SEWERS, BASEMENTS OR CONFINED AREAS.

SECTION 7 HANDLING AND STORAGE



HANDLING:

PREVENT SMALL SPILLS AND LEAKAGE TO AVOID SLIP HAZARD. MATERIAL CAN ACCUMULATE STATIC CHARGES WHICH MAY CAUSE AN ELECTRICAL SPARK (IGNITION SOURCE). WHEN THE MATERIAL IS HANDLED IN BULK, AN ELECTRICAL SPARK COULD IGNITE ANY FLAMMABLE VAPORS FROM LIQUIDS OR RESIDUES THAT MAY BE PRESENT (E.G., DURING SWITCH-LOADING OPERATIONS). USE PROPER BONDING AND/OR GROUND PROCEDURES. HOWEVER, BONDING AND GROUNDS MAY NOT ELIMINATE THE HAZARD FROM STATIC ACCUMULATION. CONSULT LOCAL APPLICABLE STANDARDS FOR GUIDANCE. ADDITIONAL REFERENCES INCLUDE AMERICAN PETROLEUM INSTITUTE 2003 (PROTECTION AGAINST IGNITIONS ARISING OUT OF STATIC, LIGHTNING AND STRAY CURRENTS) OR NATIONAL FIRE PROTECTION AGENCY 77 (RECOMMENDED PRACTICE ON STATIC ELECTRICITY) OR CENELEC CLC/TR 50404 (ELECTROSTATICS - CODE OF PRACTICE FOR THE AVOIDANCE OF HAZARDS DUE TO STATIC ELECTRICITY).

STATIC ACCUMULATOR: THIS MATERIAL IS A STATIC ACCUMULATOR.

STORAGE:

THE CONTAINER CHOICE, FOR EXAMPLE STORAGE VESSEL, MAY EFFECT STATIC ACCUMULATION AND DISSIPATION. DO NOT STORE IN OPEN OR UNLABELLED CONTAINERS.

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION



EXPOSURE LIMIT VALUES:

EXPOSURE LIMITS/STANDARDS (NOTE: EXPOSURE LIMITS ARE NOT ADDITIVE):

SUBSTANCE NAME	FORM	LIMIT / STANDARD	NOTE	SOURCE
1-DECENE, HOMOPOLYMER	AEROSOLS	TWA: 5 MG/M3	N/A	EXXONMOBIL

HYDROGENATED (THORACIC FRACTION)

TRIPHENYL PHOSPHATE TWA: 3 MG/M3 N/A OSHA Z1

TRIPHENYL PHOSPHATE TWA: 3 MG/M3 N/A ACGIH

EXPOSURE LIMITS/STANDARDS FOR MATERIALS THAT CAN BE FORMED WHEN HANDLING THIS PRODUCT:

WHEN MISTS/AEROSOLS CAN OCCUR THE FOLLOWING ARE RECOMMENDED:
5 MG/M3 - ACGIH TLV (INHALABLE FRACTION), 5 MG/M3 - OSHA PEL.

NOTE:

LIMITS/STANDARDS SHOWN FOR GUIDANCE ONLY. FOLLOW APPLICABLE REGULATIONS.

NO BIOLOGICAL LIMITS ALLOCATED.

ENGINEERING CONTROLS:

THE LEVEL OF PROTECTION AND TYPES OF CONTROLS NECESSARY WILL VARY DEPENDING UPON POTENTIAL EXPOSURE CONDITIONS.

CONTROL MEASURES TO CONSIDER:

NO SPECIAL REQUIREMENTS UNDER ORDINARY CONDITIONS OF USE AND WITH ADEQUATE VENTILATION.

PERSONAL PROTECTION:

PERSONAL PROTECTIVE EQUIPMENT SELECTIONS VARY BASED ON POTENTIAL EXPOSURE CONDITIONS SUCH AS APPLICATIONS, HANDLING PRACTICES, CONCENTRATION AND VENTILATION. INFORMATION ON THE SELECTION OF PROTECTIVE EQUIPMENT FOR USE WITH THIS MATERIAL, AS PROVIDED BELOW, IS BASED UPON INTENDED, NORMAL USAGE.

RESPIRATORY PROTECTION:

IF ENGINEERING CONTROLS DO NOT MAINTAIN AIRBORNE CONTAMINANT CONCENTRATIONS AT A LEVEL WHICH IS ADEQUATE TO PROTECT WORKER HEALTH, AN APPROVED RESPIRATOR MAY BE APPROPRIATE. RESPIRATOR SELECTION, USE, AND MAINTENANCE MUST BE IN ACCORDANCE WITH REGULATORY REQUIREMENTS, IF APPLICABLE.

TYPES OF RESPIRATORS TO BE CONSIDERED FOR THIS MATERIAL INCLUDE:

NO SPECIAL REQUIREMENTS UNDER ORDINARY CONDITIONS OF USE AND WITH ADEQUATE VENTILATION.

FOR HIGH AIRBORNE CONCENTRATIONS, USE AN APPROVED SUPPLIED-AIR RESPIRATOR, OPERATED IN POSITIVE PRESSURE MODE. SUPPLIED AIR RESPIRATORS WITH AN ESCAPE BOTTLE MAY BE APPROPRIATE WHEN OXYGEN LEVELS ARE INADEQUATE, GAS/VAPOR WARNING PROPERTIES ARE POOR, OR IF AIR PURIFYING FILTER CAPACITY/RATING MAY BE EXCEEDED.

HAND PROTECTION:

ANY SPECIFIC GLOVE INFORMATION PROVIDED IS BASED ON PUBLISHED LITERATURE AND GLOVE MANUFACTURER DATA. GLOVE SUITABILITY AND BREAKTHROUGH TIME WILL DIFFER DEPENDING ON THE SPECIFIC USE CONDITIONS. CONTACT THE GLOVE MANUFACTURER FOR SPECIFIC ADVICE ON GLOVE SELECTION AND BREAKTHROUGH TIMES FOR YOUR USE CONDITIONS. INSPECT AND REPLACE WORN OR DAMAGED GLOVES.

THE TYPES OF GLOVES TO BE CONSIDERED FOR THIS MATERIAL INCLUDE:

NO PROTECTION IS ORDINARILY REQUIRED UNDER NORMAL CONDITIONS OF USE.

EYE PROTECTION:

IF CONTACT IS LIKELY, SAFETY GLASSES WITH SIDE SHIELDS ARE RECOMMENDED.

SKIN AND BODY PROTECTION:

ANY SPECIFIC CLOTHING INFORMATION PROVIDED IS BASED ON PUBLISHED LITERATURE OR MANUFACTURER DATA.

THE TYPES OF CLOTHING TO BE CONSIDERED FOR THIS MATERIAL INCLUDE:

NO SKIN PROTECTION IS ORDINARILY REQUIRED UNDER NORMAL CONDITIONS OF USE. IN ACCORDANCE WITH GOOD INDUSTRIAL HYGIENE PRACTICES, PRECAUTIONS SHOULD BE TAKEN TO AVOID SKIN CONTACT.

SPECIFIC HYGIENE MEASURES:

ALWAYS OBSERVE GOOD PERSONAL HYGIENE MEASURES, SUCH AS WASHING AFTER HANDLING THE MATERIAL AND BEFORE EATING, DRINKING, AND/OR SMOKING.

ROUTINELY WASH WORK CLOTHING AND PROTECTIVE EQUIPMENT TO REMOVE CONTAMINANTS. DISCARD CONTAMINATED CLOTHING AND FOOTWEAR THAT CANNOT BE CLEANED. PRACTICE GOOD HOUSEKEEPING.

ENVIRONMENTAL CONTROLS:

COMPLY WITH APPLICABLE ENVIRONMENTAL REGULATIONS LIMITING DISCHARGE TO AIR, WATER AND SOIL. PROTECT THE ENVIRONMENT BY APPLYING APPROPRIATE CONTROL MEASURES TO PREVENT OR LIMIT EMISSIONS.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES



NOTE:

PHYSICAL AND CHEMICAL PROPERTIES ARE PROVIDED FOR SAFETY, HEALTH AND ENVIRONMENTAL CONSIDERATIONS ONLY AND MAY NOT FULLY REPRESENT PRODUCT SPECIFICATIONS. CONTACT THE SUPPLIER FOR ADDITIONAL INFORMATION.

GENERAL INFORMATION

PHYSICAL STATE: LIQUID

COLOR: ORANGE

ODOR: CHARACTERISTIC

ODOR THRESHOLD: N/D

IMPORTANT HEALTH, SAFETY, AND ENVIRONMENTAL INFORMATION:

RELATIVE DENSITY (AT 15 DEG. C): 0.854

FLAMMABILITY (SOLID, GAS): N/A

FLASH POINT [METHOD]: >210 DEG. C (410 DEG. F) [ASTM D-92]

FLAMMABLE LIMITS (APPROXIMATE VOLUME % IN AIR):

LEL: 0.9

UEL: 7.0

AUTOIGNITION TEMPERATURE: N/D

BOILING POINT / RANGE: >316 DEG. C (600 DEG. F)

DECOMPOSITION TEMPERATURE: N/D

VAPOR DENSITY (AIR = 1): >2 AT 101 KPA

VAPOR PRESSURE: <0.013 KPA (0.1 MMHg) AT 20 DEG. C

EVAPORATION RATE (N-BUTYL ACETATE = 1): N/D

PH: N/A

LOG POW (N-OCTANOL/WATER PARTITION COEFFICIENT): >3.5

SOLUBILITY IN WATER: NEGLIGIBLE

VISCOSITY:

220 CST (220 MM²/SEC) AT 40 DEG. C

28.5 CST (28.5 MM²/SEC) AT 100 DEG. C

OXIDIZING PROPERTIES: SEE HAZARDS IDENTIFICATION SECTION.

OTHER INFORMATION:

FREEZING POINT: N/D

MELTING POINT: N/A

POUR POINT: -36 DEG. C (-33 DEG. F)

SECTION 10 STABILITY AND REACTIVITY

REACTIVITY: SEE SUB-SECTIONS BELOW.

STABILITY: MATERIAL IS STABLE UNDER NORMAL CONDITIONS.

CONDITIONS TO AVOID: EXCESSIVE HEAT. HIGH ENERGY SOURCES OF IGNITION.

MATERIALS TO AVOID: STRONG OXIDIZERS

HAZARDOUS DECOMPOSITION PRODUCTS:
MATERIAL DOES NOT DECOMPOSE AT AMBIENT TEMPERATURES.

POSSIBILITY OF HAZARDOUS REACTIONS:
HAZARDOUS POLYMERIZATION WILL NOT OCCUR.

SECTION 11 TOXICOLOGICAL INFORMATION

INFORMATION ON TOXICOLOGICAL EFFECTS:

HAZARD CLASS	CONCLUSION / REMARKS
INHALATION:	
ACUTE TOXICITY: NO END POINT DATA FOR MATERIAL.	MINIMALLY TOXIC. BASED ON ASSESSMENT OF THE COMPONENTS.
IRRITATION: NO END POINT DATA FOR MATERIAL.	NEGLIGIBLE HAZARD AT AMBIENT/NORMAL HANDLING TEMPERATURES.
INGESTION:	
ACUTE TOXICITY: NO END POINT DATA FOR MATERIAL.	MINIMALLY TOXIC. BASED ON ASSESSMENT OF THE COMPONENTS.
SKIN:	
ACUTE TOXICITY: NO END POINT DATA FOR MATERIAL.	MINIMALLY TOXIC. BASED ON ASSESSMENT OF THE COMPONENTS.
SKIN CORROSION/IRRITATION: NO END POINT DATA FOR MATERIAL.	NEGLIGIBLE IRRITATION TO SKIN AT AMBIENT TEMPERATURES. BASED ON ASSESSMENT OF THE COMPONENTS.
EYE:	
SERIOUS EYE DAMAGE/IRRITATION: NO END POINT DATA FOR MATERIAL.	MAY CAUSE MILD, SHORT-LASTING DISCOMFORT TO EYES. BASED ON ASSESSMENT OF THE COMPONENTS.
SENSITIZATION:	
RESPIRATORY SENSITIZATION: NO END POINT DATA FOR MATERIAL.	NOT EXPECTED TO BE A RESPIRATORY SENSITIZER.
SKIN SENSITIZATION: NO END POINT DATA FOR MATERIAL.	NOT EXPECTED TO BE A SKIN SENSITIZER. BASED ON ASSESSMENT OF THE COMPONENTS.
ASPIRATION: DATA AVAILABLE.	NOT EXPECTED TO BE AN ASPIRATION HAZARD. BASED ON PHYSICO-CHEMICAL PROPERTIES OF THE MATERIAL.
GERM CELL MUTAGENICITY: NO END POINT DATA FOR MATERIAL.	NOT EXPECTED TO BE A GERM CELL MUTAGEN. BASED ON ASSESSMENT OF THE COMPONENTS.
CARCINOGENICITY: NO END POINT DATA FOR MATERIAL.	NOT EXPECTED TO CAUSE CANCER. BASED ON ASSESSMENT OF THE COMPONENTS.

REPRODUCTIVE TOXICITY:
NO END POINT DATA FOR MATERIAL. NOT EXPECTED TO BE A REPRODUCTIVE TOXICANT. BASED ON ASSESSMENT OF THE COMPONENTS.

LACTATION:
NO END POINT DATA FOR MATERIAL. NOT EXPECTED TO CAUSE HARM TO BREAST-FED CHILDREN.

SPECIFIC TARGET ORGAN TOXICITY (STOT):

SINGLE EXPOSURE:
NO END POINT DATA FOR MATERIAL. NOT EXPECTED TO CAUSE ORGAN DAMAGE FROM A SINGLE EXPOSURE.

REPEATED EXPOSURE:
NO END POINT DATA FOR MATERIAL. NOT EXPECTED TO CAUSE ORGAN DAMAGE FROM PROLONGED OR REPEATED EXPOSURE. BASED ON ASSESSMENT OF THE COMPONENTS.

OTHER INFORMATION:

CONTAINS:
SYNTHETIC BASE OILS:
NOT EXPECTED TO CAUSE SIGNIFICANT HEALTH EFFECTS UNDER CONDITIONS OF NORMAL USE, BASED ON LABORATORY STUDIES WITH THE SAME OR SIMILAR MATERIALS. NOT MUTAGENIC OR GENOTOXIC. NOT SENSITIZING IN TEST ANIMALS AND HUMANS.

THE FOLLOWING INGREDIENTS ARE CITED ON THE LISTS BELOW: NONE.

REGULATORY LISTS SEARCHED:

1 = NTP CARC
2 = NTP SUS
3 = IARC 1
4 = IARC 2A
5 = IARC 2B
6 = OSHA CARC

SECTION 12 ECOLOGICAL INFORMATION

THE INFORMATION GIVEN IS BASED ON DATA AVAILABLE FOR THE MATERIAL, THE COMPONENTS OF THE MATERIAL, AND SIMILAR MATERIALS.

ECOTOXICITY:

MATERIAL: NOT EXPECTED TO BE HARMFUL TO AQUATIC ORGANISMS.

MATERIAL:

NOT EXPECTED TO DEMONSTRATE CHRONIC TOXICITY TO AQUATIC ORGANISMS.

MOBILITY:

BASE OIL COMPONENT:
LOW SOLUBILITY AND FLOATS AND IS EXPECTED TO MIGRATE FROM WATER TO THE LAND. EXPECTED TO PARTITION TO SEDIMENT AND WASTEWATER SOLIDS.

ECOLOGICAL DATA:

ECOTOXICITY:

TEST	DURATION	ORGANISM TYPE	TEST RESULTS
AQUATIC - ACUTE TOXICITY	96 HOUR(S)	ONCORHYNCHUS MYKISS	LL50 1003 MG/L: DATA FOR SIMILAR MATERIALS
AQUATIC - CHRONIC TOXICITY	21 DAY(S)	DAPHNIA MAGNA	NOELR 1 MG/L: DATA FOR SIMILAR MATERIALS

SECTION 13 DISPOSAL CONSIDERATIONS

DISPOSAL RECOMMENDATIONS BASED ON MATERIAL AS SUPPLIED. DISPOSAL MUST BE IN ACCORDANCE WITH CURRENT APPLICABLE LAWS AND REGULATIONS, AND MATERIAL CHARACTERISTICS AT TIME OF DISPOSAL.

DISPOSAL RECOMMENDATIONS:

PRODUCT IS SUITABLE FOR BURNING IN AN ENCLOSED CONTROLLED BURNER FOR FUEL VALUE OR DISPOSAL BY SUPERVISED INCINERATION AT VERY HIGH TEMPERATURES TO PREVENT FORMATION OF UNDESIRABLE COMBUSTION PRODUCTS. PROTECT THE ENVIRONMENT. DISPOSE OF USED OIL AT DESIGNATED SITES. MINIMIZE SKIN CONTACT. DO NOT MIX USED OILS WITH SOLVENTS, BRAKE FLUIDS OR COOLANTS.

REGULATORY DISPOSAL INFORMATION:

RCRA INFORMATION:

THE UNUSED PRODUCT, IN OUR OPINION, IS NOT SPECIFICALLY LISTED BY THE EPA AS A HAZARDOUS WASTE (40 CFR, PART 261D), NOR IS IT FORMULATED TO CONTAIN MATERIALS WHICH ARE LISTED AS HAZARDOUS WASTES. IT DOES NOT EXHIBIT THE HAZARDOUS CHARACTERISTICS OF IGNITABILITY, CORROSITIVITY OR REACTIVITY AND IS NOT FORMULATED WITH CONTAMINANTS AS DETERMINED BY THE TOXICITY CHARACTERISTIC LEACHING PROCEDURE (TCLP). HOWEVER, USED PRODUCT MAY BE REGULATED.

EMPTY CONTAINER WARNING:

EMPTY CONTAINER WARNING (WHERE APPLICABLE):

EMPTY CONTAINERS MAY CONTAIN RESIDUE AND CAN BE DANGEROUS. DO NOT ATTEMPT TO REFILL OR CLEAN CONTAINERS WITHOUT PROPER INSTRUCTIONS. EMPTY DRUMS SHOULD BE COMPLETELY DRAINED AND SAFELY STORED UNTIL APPROPRIATELY RECONDITIONED OR DISPOSAL. EMPTY CONTAINERS SHOULD BE TAKEN FOR RECYCLING, RECOVERY, OR DISPOSAL THROUGH SUITABLY QUALIFIED OR LICENSED CONTRACTOR AND IN ACCORDANCE WITH GOVERNMENTAL REGULATIONS. DO NOT PRESSURISE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

SECTION 14 TRANSPORT INFORMATION



LAND (DOT): NOT REGULATED FOR LAND TRANSPORT

LAND (TDG): NOT REGULATED FOR LAND TRANSPORT

SEA (IMDG): NOT REGULATED FOR SEA TRANSPORT ACCORDING TO IMDG-CODE

MARINE POLLUTANT: NO

AIR (IATA): NOT REGULATED FOR AIR TRANSPORT

SECTION 15 REGULATORY INFORMATION



OSHA HAZARD COMMUNICATION STANDARD:

THIS MATERIAL IS NOT CONSIDERED HAZARDOUS IN ACCORDANCE WITH OSHA HAZCOM 2012, 29 CFR 1910.1200.

LISTED OR EXEMPT FROM LISTING/NOTIFICATION ON THE FOLLOWING CHEMICAL INVENTORIES: TSCA

SPECIAL CASES:

INVENTORY	STATUS
AICS	RESTRICTIONS APPLY
IECSC	RESTRICTIONS APPLY
KECI	RESTRICTIONS APPLY
NDSL	RESTRICTIONS APPLY

PRODUCT REGISTRATION STATUS: USA

EPCRA SECTION 302:

THIS MATERIAL CONTAINS NO EXTREMELY HAZARDOUS SUBSTANCES.

SARA (311/312) REPORTABLE HAZARD CATEGORIES: NONE.

SARA (313) TOXIC RELEASE INVENTORY:

THIS MATERIAL CONTAINS NO CHEMICALS SUBJECT TO THE SUPPLIER NOTIFICATION REQUIREMENTS OF THE SARA 313 TOXIC RELEASE PROGRAM.

THE FOLLOWING INGREDIENTS ARE CITED ON THE LISTS BELOW:

CHEMICAL NAME	CAS NUMBER	LIST CITATIONS
PHENOL, 4,4-METHYLENEBIS (2,6-BIS(1,1-DIMETHYLETHYL)-	118-82-1	5

REGULATORY LISTS SEARCHED:

1 = ACGIH ALL
 2 = ACGIH A1
 3 = ACGIH A2
 4 = OSHA Z
 5 = TSCA 4
 6 = TSCA 5A2
 7 = TSCA 5E
 8 = TSCA 6
 9 = TSCA 12B
 10 = CA P65 CARC
 11 = CA P65 REPRO
 12 = CA RTK
 13 = IL RTK
 14 = LA RTK
 15 = MI 293
 16 = MN RTK
 17 = NJ RTK
 18 = PA RTK
 19 = RI RTK

CODE KEY:

CARC=CARCINOGEN

REPRO=REPRODUCTIVE

SECTION 16 OTHER INFORMATION



N/D = NOT DETERMINED

N/A = NOT APPLICABLE

KEY TO THE H-CODES CONTAINED IN SECTION 3 OF THIS DOCUMENT
(FOR INFORMATION ONLY):

H304: MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS; ASPIRATION, CAT 1

H400: VERY TOXIC TO AQUATIC LIFE; ACUTE ENV TOX, CAT 1

H410:

VERY TOXIC TO AQUATIC LIFE WITH LONG LASTING EFFECTS; CHRONIC ENV TOX,
CAT 1

THIS SAFETY DATA SHEET CONTAINS THE FOLLOWING REVISIONS:

UPDATES MADE IN ACCORDANCE WITH IMPLEMENTATION OF GHS REQUIREMENTS.

THE INFORMATION AND RECOMMENDATIONS CONTAINED HEREIN ARE, TO THE BEST OF EXXONMOBIL'S KNOWLEDGE AND BELIEF, ACCURATE AND RELIABLE AS OF THE DATE ISSUED. YOU CAN CONTACT EXXONMOBIL TO INSURE THAT THIS DOCUMENT IS THE MOST CURRENT AVAILABLE FROM EXXONMOBIL. THE INFORMATION AND RECOMMENDATIONS ARE OFFERED FOR THE USER'S CONSIDERATION AND EXAMINATION. IT IS THE USER'S RESPONSIBILITY TO SATISFY ITSELF THAT THE PRODUCT IS SUITABLE FOR THE INTENDED USE. IF BUYER REPACKAGES THIS PRODUCT, IT IS THE USER'S RESPONSIBILITY TO INSURE PROPER HEALTH, SAFETY AND OTHER NECESSARY INFORMATION IS INCLUDED WITH AND/OR ON THE CONTAINER. APPROPRIATE WARNINGS AND SAFE-HANDLING PROCEDURES SHOULD BE PROVIDED TO HANDLERS AND USERS. ALTERATION OF THIS DOCUMENT IS STRICTLY PROHIBITED. EXCEPT TO THE EXTENT

REQUIRED BY LAW, RE-PUBLICATION OR RETRANSMISSION OF THIS DOCUMENT, IN WHOLE OR IN PART, IS NOT PERMITTED. THE TERM, "EXXONMOBIL" IS USED FOR CONVENIENCE, AND MAY INCLUDE ANY ONE OR MORE OF EXXONMOBIL CHEMICAL COMPANY, EXXON MOBIL CORPORATION, OR ANY AFFILIATES IN WHICH THEY DIRECTLY OR INDIRECTLY HOLD ANY INTEREST.

INTERNAL USE ONLY:
MHC: 0B, 0B, 0, 0, 0, 0
PPEC: A

DGN: 2007966XUS (1011899)

COPYRIGHT 2002 EXXON MOBIL CORPORATION, ALL RIGHTS RESERVED